

# Product datasheet

Specifications



Protection and control relay,  
PowerLogic P7, generator standard,  
5CT, 4VT, 24BI, 20BO, 110-250V,  
ethernet RJ45

REL73502

EAN Code: 3606486926611

## Main

Range of product	PowerLogic P7
Product or component type	Protection and control relay
Relay application	Generator application and bay control
product reference	P7
Mounting case size	40TE
Device mounting	Flush
Mounting support	19" rack
Mounting mode	Flush mounting Rack-mounted
power supply	110...250 V DC 110...250 V AC 50/60 Hz
measuring inputs	4 CT 1/5 A 1 CT 1 A 4 VT
number of Digital Inputs (DI)	24
number of analogue inputs	8 RTD optional
number of Digital Outputs (DO)	20 1 watchdog
type of temperature module connection	2 twisted, type A, shielded wires (RS485)
communication ports	1 CAN port 1 Ethernet TCP/IP 2 SFP ports 1 USB port 1 COM serial link
communication protocols	Modbus serial and TCP DNP3 serial and TCP IEC 61850 Ed 2.1 IEC 61869-9 IEC 61850-9-2 LE
Redundancy communication port protocol	HSR PRP RSTP Failover

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

<b>Cybersecurity</b>	<p>IEC 62443 SL2</p> <p>LDAP</p> <p>RADIUS based user authentication</p> <p>Port hardening</p> <p>Role-based access control</p> <p>Secure boot</p> <p>Security log</p> <p>Syslog protocol support</p> <p>Secured communication with associated tools</p> <p>Password protection</p> <p>Firmware signature</p> <p>Client IP address filter</p> <p>Pre-login banner</p> <p>Security policy management</p>
<b>protection functions</b>	<p>Phase overcurrent 50/51</p> <p>Ground fault protection 50N/51N</p> <p>Sensitive earth fault overcurrent 50G/51G</p> <p>Negative sequence overcurrent 46</p> <p>Inrush detection 68</p> <p>Phase undercurrent 37</p> <p>Undervoltage 27</p> <p>Overvoltage 59</p> <p>Positive sequence undervoltage 47</p> <p>Overfrequency 81O</p> <p>Underfrequency 81U</p> <p>High impedance differential 64REF</p> <p>Motor differential 87M</p> <p>Thermal overload for machines 49</p> <p>Temperature monitoring (8 or 16 RTDs) 38/49T</p> <p>Startup motoring 48</p> <p>Locked rotor 51LR</p> <p>Motor restart inhibition 66</p> <p>Voltage check 47</p> <p>Overspeed 12</p> <p>Underspeed (2 set points) 14</p> <p>Field loss (underimpedance) 40</p> <p>Underimpedance 21</p> <p>Out of step 78PS</p>
<b>measurement functions</b>	<p>Current 3-phase</p> <p>RMS current 3-phase</p> <p>Current sequence</p> <p>Current 1-phase</p> <p>RMS current 1-phase</p> <p>Voltage 3-phase</p> <p>RMS voltage 3-phase</p> <p>Voltage sequence</p> <p>Voltage 1-phase</p> <p>RMS voltage 1-phase</p> <p>Power</p> <p>Power factor maximum</p> <p>Active power fundamental frequency</p> <p>Apparent power fundamental frequency</p> <p>Reactive power fundamental frequency</p> <p>RMS active power fundamental frequency</p> <p>RMS reactive power fundamental frequency</p> <p>RMS apparent power</p> <p>Active power demand maximum</p> <p>Active power demand minimum</p> <p>Reactive power demand maximum</p> <p>Reactive power demand minimum</p> <p>Apparent power demand maximum</p> <p>Apparent power demand minimum</p> <p>RMS phase current demand maximum</p> <p>RMS phase current demand minimum</p> <p>Earth fault current external measurement</p>
<b>control functions</b>	<p>Switchgear control and monitoring</p> <p>Programmable switchgear interlocking</p> <p>Local/remote control</p> <p>Programmable logic</p> <p>Remote control</p> <p>Function keys</p>
<b>controllable switchgear devices</b>	10 controlled objects
<b>number of setting groups</b>	8

<b>monitoring functions</b>	Circuit breaker monitoring Switch monitoring Relay self-monitoring Trip circuit supervision 74 Event counters Watchdog
<b>logs and records</b>	Disturbance recording Event recording Fault recording Operation log
<b>Switchgear diagnosis type</b>	CT/VT supervision ANSI code: 60 Auxiliary power supply monitoring Cumulative breaking current Number of operations DC battery voltage monitoring
<b>Connections - terminals</b>	Screw type terminals (digital input/output) Ring terminal (analogue input)

## Complementary

<b>Input power interruption</b>	100 ms 200 ms
<b>Maximum power consumption in W</b>	24 W typical
<b>Operating threshold</b>	110 V DC 220 V DC
<b>Time synchronisation protocol</b>	IRIG-B SNTP IEEE 1588
<b>Software name</b>	PowerLogic Engineering Suite
<b>Display type</b>	Colour touchscreen 800 x 640 pixels
<b>Display size</b>	7 inch
<b>Information displayed</b>	Single line diagram Menu-driven user interface
<b>Control button type</b>	1 home physical key 1 reset physical key 12 customizable virtual function keys
<b>Local signalling</b>	4 LEDs red/orange device status 24 LEDs tri-colour programmable
<b>Communication compatibility</b>	DNP3 Modbus IEC 61850 Ed 2.1
<b>Device connection</b>	Connection to a PC USB Extension port extension cable Ethernet port RJ45 Serial port RS485 cable SFP redundant Ethernet port fibre optic/RJ45 multi/single mode optional
<b>Product certifications</b>	cUL listed UKCA KETOP CE DNV
<b>Height</b>	178 mm
<b>Width</b>	205.2 mm
<b>Depth</b>	282 mm
<b>Net weight</b>	8.8 kg maximum

## Environment

<b>climatic withstand</b>	Exposure to cold Ae conforming to IEC 60068-2-1 Exposure to dry heat Be conforming to IEC 60068-2-2 Exposure to damp heat in service Cab conforming to IEC 60068-2-78 Temperature variation Nb conforming to IEC 60068-2-14 Exposure to damp heat not in service Cab conforming to IEC 60068-2-30 Salt mist Kb/1 conforming to IEC 60068-2-52 Influence of corrosion/gas test 2 Ke conforming to IEC 60068-2-60 Influence of corrosion/gas test 4 Ke conforming to IEC 60068-2-60
<b>Mechanical robustness</b>	Vibrations (level: class 2) conforming to IEC 60255-21-1 Shocks (level: class 2) conforming to IEC 60255-21-2 Shocks (level: class 1) conforming to IEC 60255-21-2 Bumps (level: class 1) conforming to IEC 60255-21-2 Seismic tests (level: class 2) conforming to IEC 60255-21-3
<b>Electromagnetic compatibility</b>	Electromagnetic immunity class A conforming to CISPR 11 Electromagnetic immunity class A conforming to CISPR 22 Electromagnetic immunity level 3 conforming to IEC 6100-4-3 Radiated radio-frequency electromagnetic field immunity test level 4 conforming to ANSI C37.90.2 Electrostatic discharge level 4 conforming to IEC 6100-4-2 Electrostatic discharge level 5 conforming to ANSI C37.90.3 Immunity to magnetic fields level 4 conforming to IEC 61000-4-8 Immunity to magnetic fields level 5 conforming to IEC 61000-4-9 Immunity to magnetic fields level 5 conforming to IEC 61000-4-10 Conducted RF disturbances level 3 conforming to IEC 61000-4-6 Fast transient bursts level 4 conforming to IEC 61000-4-4 Damped oscillatory wave level 3 conforming to IEC 61000-4-18 Damped oscillatory wave level 4 conforming to ANSI C37.90.1 Damped oscillatory wave level 3 conforming to IEC 61000-4-12 Conducted disturbance emission A conforming to IEC 61000-4-16 Surges level 4 conforming to IEC 61000-4-5
<b>Ambient air temperature for operation</b>	-40...70 °C ( 96 h )
<b>IP degree of protection</b>	IP54 front conforming to IEC 60529 IP30 case conforming to IEC 60529 IP20 rear conforming to IEC 60529
<b>IK degree of protection</b>	IK07 conforming to IEC 62262
<b>maximum operating altitude</b>	2000 m
<b>Protective treatment</b>	Conformal coating conforming to IEC 60068-2-52:Kb/1 Conformal coating conforming to IEC 60068-2-60:Ke
<b>Relative humidity</b>	0...93 % at 40 °C, without condensation, 56 days

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	30 cm
<b>Package 1 Width</b>	30 cm
<b>Package 1 Length</b>	40 cm
<b>Package 1 Weight</b>	8.217 kg

## Contractual warranty

<b>Warranty</b>	Up to 10 years extended warranty (Standard warranty 2 years. Please check with your local SE representative for extended warranty availability and conditions)
-----------------	--

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	<b>1709</b>
---	-------------

Environmental Disclosure	<a href="#">Product Environmental Profile</a>
--------------------------	---

## Use Better

### Materials and Substances

Packaging made with recycled cardboard	<b>Yes</b>
--	------------

Packaging without single use plastic	<b>No</b>
--------------------------------------	-----------

EU RoHS Directive	<b>Compliant with Exemptions</b>
-------------------	----------------------------------

SCIP Number	<b>7185a990-e1e7-4906-8102-573086cf8d7d</b>
-------------	---

REACH Regulation	<a href="#">REACH Declaration</a>
------------------	-----------------------------------

China RoHS Regulation	<a href="#">China RoHS declaration</a>
-----------------------	--

## Use Again

### Repack and remanufacture

Circularity Profile	<a href="#">End of Life Information</a>
---------------------	---

WEEE



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

---

Take-back

No

---