

# Product datasheet

Specifications



## PowerLogic™ P5V20 24-250V 4VT 10DI-8DO

REL50306

EAN Code: 3606489487874

### Main

Range of product	PowerLogic P5
Product or component type	Protection and control relay
Relay application	Voltage
product reference	P5V20-AABB-DAAAA-BAEA
Mounting case size	20TE
Device mounting	Flush
Mounting mode	Withdrawable
power supply	24...240 V DC 100...230 V AC
measuring inputs	: VT voltage 4
Number of sensors	0 temperature sensor(s) 0 arc sensor(s)
number of Digital Inputs (DI)	10
number of analogue inputs	0
number of Digital Outputs (DO)	7 DO 1 watchdog
number of analogue outputs	0
communication ports	USB port 2 front
communication protocols	-
Cybersecurity	Port hardening Firmware signature Client IP address filter Secured communication with associated tools Security policy management Role-based access control Security log LDAP RADIUS based user authentication IEC 62443-4-2 SL1
protection functions	Overvoltage Undervoltage Positive sequence undervoltage 27P Earth fault overvoltage 59N Underfrequency 81/81N Rate of change of frequency 81R Synchro-check Breaker failure 50BF Lockout relay VT supervision Programmable stages Programmable curve

<b>measurement functions</b>	Voltage 3-phase Voltage residual Voltage zero sequence Voltage positive sequence Voltage negative sequence Frequency Phasor diagram of currents or voltages
<b>control functions</b>	Switchgear control and monitoring Programmable switchgear interlocking Local/remote control
<b>controllable switchgear devices</b>	6 controlled + 2 monitored objects
<b>number of setting groups</b>	4
<b>monitoring functions</b>	Trip circuit supervision 74 Circuit breaker monitoring Relay self-monitoring
<b>logs and records</b>	Event recording Disturbance recording Tripping context Relay maintenance
<b>Switchgear diagnosis type</b>	VT supervision ANSI code: 60 Trip circuit supervision ANSI code: 74
<b>Connections - terminals</b>	Screw (digital input/output) Ring lugs (analog inputs and outputs)

## Complementary

<b>Software name</b>	ESetup Easergy Pro: virtual simulation test
<b>Display type</b>	LCD 192 x 96 pixels
<b>Number of key</b>	1 customizable
<b>Local signalling</b>	4 x LED 6 x LED tri-colour programmable
<b>Height</b>	176 mm
<b>Width</b>	102 mm
<b>Depth</b>	219 mm
<b>Net weight</b>	2.5 kg

## Environment

<b>climatic withstand</b>	Exposure to cold conforming to IEC 60068-2-1 Exposure to dry heat conforming to IEC 60068-2-2 Exposure to damp heat in service conforming to IEC 60068-2-78 Exposure to damp heat in service conforming to IEC 60068-2-30 Temperature variation conforming to IEC 60068-2-14 Salt mist conforming to IEC 60068-2-52 Influence of corrosion/gas test 2 conforming to IEC 60068-2-60 Influence of corrosion/gas test 4 conforming to IEC 60068-2-60 Influence of corrosion/gas test 2 conforming to IEC 60721-3-3 Influence of corrosion/gas test 4 conforming to IEC 60721-3-3
<b>Mechanical robustness</b>	Vibrations (level: class 2) conforming to IEC 60255-21-1 Vibrations conforming to GOST 17516.1 Vibrations conforming to IACS E10 Shocks (level: class 2) conforming to IEC 60255-21-2 Earthquakes (level: class 2) conforming to IEC 60255-21-3

<b>Electromagnetic compatibility</b>	<p>Emission tests class A conforming to CISPR 11  Emission tests class A conforming to CISPR 32  Emission tests conforming to IACS E10  EMC immunity class 4 conforming to IEC 61000-4-2  EMC immunity class 4 conforming to ANSI C37.90.3  EMC immunity level 3 conforming to IEC 61000-4-3  EMC immunity conforming to ANSI C37.90.2  EMC immunity conforming to GOST 32137  EMC immunity conforming to GOST 30804.4.3  EMC immunity conforming to IACS E10  EMC immunity level 5 conforming to IEC 61000-4-8  EMC immunity level 5 conforming to IEC 61000-4-9  EMC immunity level 5 conforming to IEC 61000-4-10  EMC immunity level 3 conforming to IEC 61000-4-6  EMC immunity level 3 conforming to IEC 61000-4-18  EMC immunity conforming to ANSI C37.90.1  EMC immunity conforming to IEC 61000-4-12  EMC immunity conforming to GOST 30804.4.12  EMC immunity level 4 conforming to IEC 61000-4-16  EMC immunity level 4 conforming to IEC 61000-4-4  EMC immunity level 4 conforming to IEC 61000-4-5</p>
<b>Ambient air temperature for operation</b>	<p>-40...85 °C ( 16 h )  -40...70 °C ( 96 h )</p>
<b>IP degree of protection</b>	IP54 conforming to IEC 60529
<b>maximum operating altitude</b>	2000 m
<b>Protective treatment</b>	<p>Conformal coating conforming to IEC 60068-2-52:Kb/1  Conformal coating conforming to IEC 60068-2-60:Ke  Conformal coating conforming to IEC 60721-3-3:3C2</p>
<b>Relative humidity</b>	<p>0...93 % at 40 °C, without condensation, 56 days  93...95 % at 25...55 °C, 6 cycles, 12 + 12 hours</p>

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	30.0 cm
<b>Package 1 Width</b>	30.0 cm
<b>Package 1 Length</b>	40.0 cm
<b>Package 1 Weight</b>	3.0 kg

## Contractual warranty

<b>Warranty</b>	Up to 10 years extended warranty (Standard warranty 2 years. Please check with your local SE representative for extended warranty availability and conditions)
-----------------	--

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	<b>182</b>
---	------------

Environmental Disclosure	<a href="#">Product Environmental Profile</a>
--------------------------	---

## Use Better

### Materials and Substances

Packaging made with recycled cardboard	<b>Yes</b>
--	------------

Packaging without single use plastic	<b>No</b>
--------------------------------------	-----------

EU RoHS Directive	<b>Pro-active compliance (Product out of EU RoHS legal scope)</b>
-------------------	---

REACH Regulation	<a href="#">REACH Declaration</a>
------------------	-----------------------------------

China RoHS Regulation	<a href="#">China RoHS declaration</a>
-----------------------	--

## Use Again

### Repack and remanufacture

Circularity Profile	<a href="#">End of Life Information</a>
---------------------	---

WEEE



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

---

Take-back

No

---