

Product datasheet

Specifications



PowerLogic™ P5V20 4VT 24-250V 4DI-4DO RSTP Eth RJ45

REL50339

EAN Code: 3606481207883

Main

Range of product	PowerLogic P5
Product or component type	Protection and control relay
Relay application	Voltage
product reference	P5V20-AABA-DABAH-BAEA
Mounting case size	20TE
Device mounting	Flush
Mounting mode	Withdrawable
power supply	24...240 V DC 100...230 V AC
measuring inputs	: VT voltage 4
Number of sensors	0 temperature sensor(s) 0 arc sensor(s)
number of Digital Inputs (DI)	4
number of analogue inputs	0
number of Digital Outputs (DO)	3 DO 1 watchdog
number of analogue outputs	0
communication ports	RJ45 2 rear Extension port 1 rear with backup memory USB port 2 front
communication protocols	IEC 61850 ed. 1 IEC 61850 ed. 2 DNP3 over ethernet Modbus TCP EtherNet/IP
Cybersecurity	Port hardening Firmware signature Client IP address filter Secured communication with associated tools Security policy management Role-based access control Security log LDAP RADIUS based user authentication IEC 62443-4-2 SL1

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

protection functions	Overvoltage Undervoltage Positive sequence undervoltage 27P Earth fault overvoltage 59N Underfrequency 81/81N Rate of change of frequency 81R Synchro-check Breaker failure 50BF Lockout relay VT supervision Programmable stages Programmable curve
measurement functions	Voltage 3-phase Voltage residual Voltage zero sequence Voltage positive sequence Voltage negative sequence Frequency Phasor diagram of currents or voltages
control functions	Switchgear control and monitoring Programmable switchgear interlocking Local/remote control
controllable switchgear devices	6 controlled + 2 monitored objects
number of setting groups	4
monitoring functions	Trip circuit supervision 74 Circuit breaker monitoring Relay self-monitoring
logs and records	Event recording Disturbance recording Tripping context Relay maintenance
Switchgear diagnosis type	VT supervision ANSI code: 60 Trip circuit supervision ANSI code: 74
Connections - terminals	Screw (digital input/output) Ring lugs (analog inputs and outputs)

Complementary

Time synchronisation protocol	SNTP
Software name	EcoStruxure Power Device ESetup Easergy Pro: virtual simulation test
Web server	Embedded HTTP server
Display type	LCD 192 x 96 pixels
Number of key	1 customizable
Local signalling	4 x LED 6 x LED tri-colour programmable
Height	176 mm
Width	102 mm
Depth	219 mm
Net weight	2.5 kg

Environment

climatic withstand	<p>Exposure to cold conforming to IEC 60068-2-1</p> <p>Exposure to dry heat conforming to IEC 60068-2-2</p> <p>Exposure to damp heat in service conforming to IEC 60068-2-78</p> <p>Exposure to damp heat in service conforming to IEC 60068-2-30</p> <p>Temperature variation conforming to IEC 60068-2-14</p> <p>Salt mist conforming to IEC 60068-2-52</p> <p>Influence of corrosion/gas test 2 conforming to IEC 60068-2-60</p> <p>Influence of corrosion/gas test 4 conforming to IEC 60068-2-60</p> <p>Influence of corrosion/gas test 2 conforming to IEC 60721-3-3</p> <p>Influence of corrosion/gas test 4 conforming to IEC 60721-3-3</p>
Mechanical robustness	<p>Vibrations (level: class 2) conforming to IEC 60255-21-1</p> <p>Vibrations conforming to GOST 17516.1</p> <p>Vibrations conforming to IACS E10</p> <p>Shocks (level: class 2) conforming to IEC 60255-21-2</p> <p>Earthquakes (level: class 2) conforming to IEC 60255-21-3</p>
Electromagnetic compatibility	<p>Emission tests class A conforming to CISPR 11</p> <p>Emission tests class A conforming to CISPR 32</p> <p>Emission tests conforming to IACS E10</p> <p>EMC immunity class 4 conforming to IEC 61000-4-2</p> <p>EMC immunity class 4 conforming to ANSI C37.90.3</p> <p>EMC immunity level 3 conforming to IEC 61000-4-3</p> <p>EMC immunity conforming to ANSI C37.90.2</p> <p>EMC immunity conforming to GOST 32137</p> <p>EMC immunity conforming to GOST 30804.4.3</p> <p>EMC immunity conforming to IACS E10</p> <p>EMC immunity level 5 conforming to IEC 61000-4-8</p> <p>EMC immunity level 5 conforming to IEC 61000-4-9</p> <p>EMC immunity level 5 conforming to IEC 61000-4-10</p> <p>EMC immunity level 3 conforming to IEC 61000-4-6</p> <p>EMC immunity level 3 conforming to IEC 61000-4-18</p> <p>EMC immunity conforming to ANSI C37.90.1</p> <p>EMC immunity conforming to IEC 61000-4-12</p> <p>EMC immunity conforming to GOST 30804.4.12</p> <p>EMC immunity level 4 conforming to IEC 61000-4-16</p> <p>EMC immunity level 4 conforming to IEC 61000-4-4</p> <p>EMC immunity level 4 conforming to IEC 61000-4-5</p>
Ambient air temperature for operation	<p>-40...85 °C (16 h)</p> <p>-40...70 °C (96 h)</p>
IP degree of protection	IP54 conforming to IEC 60529
maximum operating altitude	2000 m
Protective treatment	<p>Conformal coating conforming to IEC 60068-2-52:Kb/1</p> <p>Conformal coating conforming to IEC 60068-2-60:Ke</p> <p>Conformal coating conforming to IEC 60721-3-3:3C2</p>
Relative humidity	<p>0...93 % at 40 °C, without condensation, 56 days</p> <p>93...95 % at 25...55 °C, 6 cycles, 12 + 12 hours</p>

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	13.5 cm
Package 1 Width	27.0 cm
Package 1 Length	37.0 cm
Package 1 Weight	2.8 kg

Contractual warranty

Warranty	Up to 10 years extended warranty (Standard warranty 2 years. Please check with your local SE representative for extended warranty availability and conditions)
-----------------	--

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	187
---	------------

Environmental Disclosure

[Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard	Yes
--	------------

Packaging without single use plastic	No
--------------------------------------	-----------

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
-------------------	---

REACH Regulation	REACH Declaration
------------------	-----------------------------------

China RoHS Regulation	China RoHS declaration
-----------------------	--

Use Again

Repack and remanufacture

Circularity Profile

[End of Life Information](#)

WEEE



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Take-back

No
